Product Information



Two Stroke Engine Oil according to NMMA TC-W2

Product Code: 124 (Jan, 2008)

Description

is a low ash, self mixing 2-stroke engine oil for use in high performance water-cooled marine outboard engines. The product is carefully formulated to protect the engine against spark plug bearing fouling, exhaust port blockage and corrosion.

Application

Product meets NMMA TC-W2 specification and is suitable in all high performance marine outboard engines where this level of performance is required.

The product should be pre-mixed with gasoline at a ratio of 50:1 or according to the manufacturer's recommendation. A special diluent in the product assists the oil in dispersing evenly throughout the gasoline. The product is dyed blue to indicate its presence in gasoline.

offers the following benefits:

- Ensures smooth engine performance.
- Extends spark plug life.
- Protects against internal engine corrosion.
- Easy mixing.

Product Characteristics*

Properties	Units	Value	Test Method
Colour		Blue	
Density @ 35 oC	kg/m3	870	ASTM D-4052
Viscosity @ 40 oC	mm2/s	83.3	ASTM D-445
@ 100 oC	mm2/s	10.44	ASTM D-445
Viscosity Index		109	ASTM D-2270
Flash Point, COC	ے ع	146	ASTM D-92
Pour Point	0	- 24	ASTM D-97

*The information and figures given here are typical of current production and conform to specification, minor variations may occur.

Manufactured by Alkarim for Trade & Industry Tel.+963 933 230 691 E-mail: radanedal75@gmail.com